

FR 3002/S

WERTHER AIR CONDITIONING

- Automatic unit for recovery
- Vacuum and recharge with electronic scales for refrigerant and oil. Suitable for big circuits



GAS
R 134-A



CE | EAC

TECHNICAL DATA

Vacuum pump	7 CFM
Storage Cylinder	40 Lt
Recovery rate	400 g/min
Charging pipes	300 cm
Size	45x95x127 cm
Gross Weight	127 kg
Manometer	63mm
Tracer	Optional
Leaks detector	YES
Cylinder Manometer	YES
Voltage	230V - 50 Hz - 1ph

ACCESSORIES



P.N 1697000026
Blue pipe 5 m



P.N 1697000030
Red pipe 5 m










P.N 1697000029
Tracer



P.N 1697000028
Leakage detector

FEATURES

-  LCD display with instructions available in 13 different languages. Italian, English, French, Spanish, German, Portuguese, Turk, Polish, Hungarian, Dutch, Swedish, Russian, Estonian, POSSIBILITY Serbian and Croatian.
-  Full automatic operations
-  Cars, buses, tractors, trucks data base, as a standard
-  Automatic control of leaks
-  40 liters tank
-  Top precision thanks to its 24 bit analogical digital converter
-  300 cm pipes as a standard