






# PL801 | 800 kg



-  Sollevatore idraulico per ruote singole o gemellari
-  Hydraulic wheel dolly for simple or twin wheels
-  Hydraulischer Zwillingsrad-Hubwagen für Einfach- oder Zwillingsräder
-  Chariot dépose roues pour roues simples où jumelées
-  Elevador hidráulico para ruedas individuales o gemelas





Dati tecnici	Technical data	Technische Eigenschaften	Caractéristiques techniques	Datos técnicos	
Portata	Capacity	Hubkraft	Capacité	Capacidad de carga	800 kg
Altezza minima	Min. lifting height	Min. Hubhöhe	Hauteur mini	Altura mínima	140 mm
Altezza massima	Max. lifting height	Max. Hubhöhe	Hauteur maxi	Altura máxima	660 mm
Interasse rulli	Distance between the wheel lifting rollers	Achsabstand Hubrollen	Distance entre les routeaux	Distancia entre ejes rodillos	min. 470 - max 740 mm
Comando a leva / pompa a semplice effetto	Single action pump / with lifting lever	Bedienungshebel / Einfachwirkende Pumpee	Levier de commande / Pompe simple effet	Mando por palanca / Bomba de acción simple	
Sicurezza idraulica in caso di sovraccarico	Overload safety valve	Überlastsicherung	Soupape de sécurité en cas de surcharge	Seguridad hidráulica en caso de sobrecarga	
Temperatura di lavoro	Working temperature	Arbeitstemperatur	Température de travail	Temperatura de trabajo	-10/+40°C
Dimensioni	Dimensions	Abmessungen	Dimensions	Medidas	1020x930x1130 mm
Peso	Weight	Gewicht	Poids	Peso	130 kg
Ruote pivotanti	Heavy duty castors for manoeuvrability	Lenkräder für Manövrierfähigkeit	Roues pivotantes	Ruedas pivotantes	

